

## PERNO HEXAGONAL METRICO ISO 4.8

Código	Diámetro	Largo "L", pulg	Envase	Entre Caras "A", mm	Altura, mm Cabeza "H"	Torque Lb-F (Nm)	Perforación Guía (*)	Largo rosca Min., mm
<b>Pavonado</b>								
201PHM	M6-1.0	10	100 U	10.0	4.0	4.3 (5.8)	5,2	Total
202PHM	M6-1.0	15						
203PHM	M6-1.0	20						
204PHM	M6-1.0	25						
205PHM	M6-1.0	30						
206PHM	M6-1.0	35						
207PHM	M6-1.0	40						
208PHM	M6-1.0	45						
209PHM	M6-1.0	50						
210PHM	M6-1.0	55						
211PHM	M6-1.0	60						
212PHM	M6-1.0	65						
280PHM	M6-1.0	70						
281PHM	M6-1.0	80						
213PHM	M8-1.25	10	100 U	13.0	5.5	11.5 (15.6)	6,9	Total
214PHM	M8-1.25	15						
215PHM	M8-1.25	20						
216PHM	M8-1.25	25						
217PHM	M8-1.25	30						
218PHM	M8-1.25	35						
219PHM	M8-1.25	40						
220PHM	M8-1.25	45						
221PHM	M8-1.25	50						
222PHM	M8-1.25	55						
223PHM	M8-1.25	60						
224PHM	M8-1.25	65						
225PHM	M8-1.25	70						
282PHM	M8-1.25	80						
226PHM	M10-1.50	20	100 U	17.0	7.0	22.4 (30.4)	8,7	Total
227PHM	M10-1.50	25						
228PHM	M10-1.50	30						
229PHM	M10-1.50	35						
230PHM	M10-1.50	40						
231PHM	M10-1.50	45						
232PHM	M10-1.50	50						
233PHM	M10-1.50	55						
234PHM	M10-1.50	60						
235PHM	M10-1.50	65						
236PHM	M10-1.50	70						
237PHM	M10-1.50	80						
238PHM	M12-1.75	20						
239PHM	M12-1.75	25	100 U	19.0	8.0	39.0 (52.9)	10,4	Total
240PHM	M12-1.75	30						
241PHM	M12-1.75	35						
242PHM	M12-1.75	40						
243PHM	M12-1.75	45						
244PHM	M12-1.75	50						
245PHM	M12-1.75	55						
246PHM	M12-1.75	60						
247PHM	M12-1.75	65						
248PHM	M12-1.75	70						
249PHM	M12-1.75	80						
250PHM	M14-2.00	30						
251PHM	M14-2.00	40						
252PHM	M14-2.00	45						
253PHM	M14-2.00	50						
254PHM	M14-2.00	60						
255PHM	M14-2.00	80						
256PHM	M16-2.00	30						
257PHM	M16-2.00	40	50 U					Total



258PHM	M16-2.00	45	25	U	24.0	10.0	94 (127.4)	14,2	38
259PHM	M16-2.00	50							
260PHM	M16-2.00	55							
261PHM	M16-2.00	60							
262PHM	M16-2.00	65							
263PHM	M16-2.00	70							
264PHM	M16-2.00	75							
265PHM	M16-2.00	80							
266PHM	M16-2.00	90							
267PHM	M16-2.00	100							
268PHM	M18-2.50	40	25	U	27.0	12,0	130 (176.3)	15,7	Total
269PHM	M18-2.50	50							
270PHM	M18-2.50	60							
271PHM	M18-2.50	70	10	U	30.0	13.0	184 (249.5)	17,7	42
272PHM	M18-2.50	80							
273PHM	M20-2.50	50	10	U	30.0	13.0	184 (249.5)	17,7	46
274PHM	M20-2.50	60							
275PHM	M20-2.50	70							
276PHM	M20-2.50	80							
277PHM	M20-2.50	90							
278PHM	M20-2.50	100							
279PHM	M20-2.50	120							

#### Zincado Brillante

B201PHM	M6-1.0	10	100	U	10.0	4.0	4.3 (5.8)	5,2	Total
B202PHM	M6-1.0	15							
B203PHM	M6-1.0	20							
B204PHM	M6-1.0	25							
B205PHM	M6-1.0	30							
B206PHM	M6-1.0	35							
B207PHM	M6-1.0	40							
B209PHM	M6-1.0	50							
B213PHM	M8-1.25	10	100	U	13.0	5.5	11.5 (15.6)	6,9	Total
B214PHM	M8-1.25	15							
B215PHM	M8-1.25	20							
B216PHM	M8-1.25	25							
B217PHM	M8-1.25	30							
B219PHM	M8-1.25	40							
B220PHM	M8-1.25	45							
B221PHM	M8-1.25	50							
B223PHM	M8-1.25	60							
B225PHM	M8-1.25	70							
B282PHM	M8-1.25	80							
B226PHM	M10-1.50	20	100	U	17.0	7.0	22.4 (30.4)	8,7	Total
B227PHM	M10-1.50	25							
B228PHM	M10-1.50	30							
B229PHM	M10-1.50	35							
B230PHM	M10-1.50	40							
B232PHM	M10-1.50	50							
B234PHM	M10-1.50	60							
B237PHM	M10-1.50	80							
B239PHM	M12-1.75	25	100	U	19.0	8.0	39 (52.9)	10,4	Total
B240PHM	M12-1.75	30							
B241PHM	M12-1.75	35							
B242PHM	M12-1.75	40							
B244PHM	M12-1.75	50							
B246PHM	M12-1.75	60							
B249PHM	M12-1.75	80	50	U				30	

(\*) Diámetros en perforación para pasar machos de roscado

